

MATERIAL SAFETY DATA SHEET
ChemCo Systems, Inc., 2800 Bay Road, Redwood City, CA 94063
Prepared by Dept. of Safety, Phone: 650/261-3790
24 Hour Emergency Phone: 800/424-9300 CHEMTREC

1. PRODUCT NAME:

KEMKO® 036, Marine Structure Coat, Part A

Chemical Family: Epoxy resin, filler mixture.

2. HAZARDOUS INGREDIENTS

| NAME | CAS No. | TLV | STEL | PEL | CONTENT |
|-------------|------------|------|------|------|---------|
| Epoxy resin | 25068-38-6 | none | none | none | 35-45% |

reference section 7, Health Hazard Data for LD (50)

3. PHYSICAL DATA:

| | | | |
|-----------------------|-------------|-------------------------------------|------|
| Boiling Point: | > 500 F | Water/Oil Distribution Coefficient: | N/D |
| Percent Volatile: | N/D | Solubility in Water: | Nil |
| Freezing Point: | N/D | Specific Gravity: | 1.8 |
| Vapor Pressure @ 20C: | N/D | pH: | N/D |
| Vapor Density: | N/D | Evaporation Rate: | N/D |
| Odor Threshold: | N/D | Odor: | Mild |
| Appearance: | White Paste | | |

N/D = Not Determined

4. FIRE AND EXPLOSION HAZARD DATA:

HMIS Hazard rating: 0 - (Least Hazard)
Flash Point: 480 F (PMCC)
Auto Ignition Temperature: N/D
Limits of Flammability: LEL: Not applicable UEL: Not applicable

EXTINGUISHING MEDIA:

CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG

SPECIAL FIRE & UNUSUAL HAZARDS:

At high temperatures vapors can cause pressure build-up in sealed containers. Use water to cool containers exposed to fire. Self-contained respirator equipment and full protective clothing required when smoke or fumes are generated. Electrical grounding not recommended.

5. REACTIVITY DATA:

HMIS Reactivity Rating: 0 - (Least Hazard)

STABILITY: This product requires another component to react at room temperature. Excessive heat and fume generation can occur if improperly handled. Not sensitive to mechanical impact.

INCOMPATIBILITY: Strong acids, strong bases. Amines and mercaptans may initiate possible hazardous polymerization.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and dioxide, aldehydes, various hydrocarbons from incomplete combustion.

HAZARDOUS POLYMERIZATION: May occur is product is not handled per instructions.

6. ENVIRONMENTAL AND DISPOSAL INFORMATION:

ACTION TO TAKE FOR SPILLS AND LEAKS: Ventilate area. Wear appropriate protective gear. Contain leak/spill. Salvage. Clean up residue with absorbent material.

WASTE DISPOSAL METHOD: Handle disposal of waste material in manner which complies with local, state, province, and federal regulations. Landfill if solidified or incinerate at agency approved waste-disposal facility.

7. HEALTH HAZARD DATA:

HMIS Hazard Rating: 2 - (Moderate Hazard)
Primary Route Of Entry: Dermal, eyes.

Effects of Overexposure:

Skin Contact: Prolonged or repeated exposure may cause skin irritation and redness. Skin sensitization or allergic reaction may occur in some individuals.

Eyes: Contact may cause irritation, redness, tearing and blurred vision.

Inhalation: Because of its low vapor pressure, this product is not likely to be an inhalation hazard.

Ingestion: Low oral toxicity.
LD (50) CAS 25068-38-6 11.4 g/kg (rat)

Chronic: Preexisting skin and eye disorders may be aggravated by this product.

8. FIRST AID:

Inhalation: Remove victim from exposure. If difficulty with breathing; administer oxygen and seek immediate medical assistance.

Eyes: Flush with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.

Skin: Remove contaminated clothing. Wash with soap and water; get medical attention if irritation persists.

Ingestion: Do not induce vomiting; give large quantities of water; get immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person.

9. SPECIAL PROTECTION INFORMATION:

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to prevent build-up of heavy vapors.

Personal Protection: Use eye protection. Selection of specific items such as gloves, boots and apron will depend on the operation. Wear respiratory protection. Whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for the listed hazard. Confined spaces, rooms or tanks are areas where concern for TLV's is especially important. Reference OSHA Reg. CFR 20 1910.134 for recommended protection.

10. ADDITIONAL INFORMATION:

DOT Proper Shipping Name: Epoxy resin mixture

DOT Hazard Class or Division: Not regulated

Identification Number: N/A

Packing Group: N/A

Labels Required: N/A

WHMIS Classification: Class D, Div. 2, Sub. B.

WHMIS Labeling: Stylized T

Storage Conditions: Keep containers tightly sealed. Store in dry and cool areas. Avoid freezing conditions.

Shelf life: Indefinite.

Special Instructions: Storage recommendations: Store at room temperature. Do not allow to freeze.

The information given herein is given in good faith. No warranty, expressed or implied, is made regarding the accuracy of these data or the results obtained from the use thereof. All materials may present unknown health hazards and must be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Consult ChemCo Systems Inc. for further information.

MSDS036A 7/99